



Product Specification

Manufacturer: SolarBright- Clean Energy Products Pty Ltd
 11 Progress Circuit Prestons NSW 2170
 Tel: 1300 852 622 - Email: info@solarbright.com.au

Product: Tubular Skylight Maxlight® Commercial Series

Features: Solar Bright Maxlight Commercial range.

Product Codes: ML550

Components List

Roof Dome	<ul style="list-style-type: none"> Hail resistant Crystal clear surface for maximum performance UV stabilised. Optional Inner disc
Roof Flashing	a variety of non-corrosive flashings, leak proof designed to suit tile, Colourbond and other metal roof profiles
Adjustable Tube (Angle Adaptors)	Durable anodized solid aluminium, 0.5 mm thickness, 300mm long top adaptor and 300mm long bottom adaptor, specular reflectance 98%, adjustable 30 degree; tubing is anodised for high protection from prolonged sun exposure and is not laminated. It will not yellow, fade or delaminate.

Extension Tubes (ordered separately)	Durable solid aluminium, 0.5 mm thickness, 400mm or 600mm long, specular reflectance 98%, tubing is anodised for high protection from prolonged sun exposure and is not laminated. It will not yellow, fade or delaminate.
Ceiling Finish – Square transition Box	White square transition box from round tube to square 605mm x 605mm ceiling diffuser to suit suspended grid or gyprock ceilings.
Diffuser Assembly	Multi-layer, square with white frame and optional finish of Aurora Fresnel lens, Prismax OR Warm
Accessories	Fasteners, Seals, Adhesive tape supplied with product by the manufacturer. Dimmers sold separately
Warranty	Industry leading 20 Year warranty



Energy Rating & Compliance	<ul style="list-style-type: none"> • Tested by NFRC approved laboratory • Meets Australian standard AS4825-2007. • Meets Building Code Australia requirements 		
	Performance	SHGC	U-Factor
	550ML	0.24	1.66
Country of origin	Australian owned, designed and made		



